Printing date 16.03.2020 Revision: 05.10.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: 40-1706-10 Ethanol Spray (70% Ethanol)
- **Registration number** 01-2119457610-43
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Product category PC21 Laboratory chemicals
- · Application of the substance / the mixture Laboratory chemical.
- · Uses advised against

Processes involving extreme heat use advised against.

Any use carrying a risk of direct contact with eyes/skin where workers are exposed without adequate personal protective equipment (PPE).

Any use involving aerosol formation or vapour or dust release in excess of the assigned workplace exposure limits where workers are exposed without suitable respiratory protective equipment (RPE).

Processes involving the use of incompatible substances - refer to section 10.

The product is stictly intended for industrial or professional use only.

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Severn Biotech Ltd.

Unit 2.

Park Lane.

Kidderminster,

Worcestershire.

DY11 6TJ

UK

Tel: 0044 1562 825286 Fax: 0044 1562 825284 email: info@severnbiotech.com

- · Further information obtainable from: Product safety department.
- 1.4 Emergency telephone number: Tel: 0044 1562 825286 (not 24 hours)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS07
- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P280 Wear protective gloves / eye protection.

(Contd. on page 2)

Printing date 16.03.2020 Revision: 05.10.2018

Trade name: 40-1706-10 Ethanol Spray (70% Ethanol)

(Contd. of page 1)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: An aqueous solution of ethanol
- · Dangerous components:

CAS: 64-17-5 Ethanol EINECS: 200-578-6

Flam. Liq. 2, H225; Eye Irrit. 2, H319

70%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

DO NOT DELAY!

Check for and remove any contact lenses.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- · Information for doctor: Treat symptomatically and supportively.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture Flammable liquid and vapour.
- · 5.3 Advice for firefighters
- · Protective equipment:

Wear fully protective suit.

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

· Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Be aware of possibility of re-ignition.

This product gives off flammable vapours which may form explosive mixtures with air.

Vapours with a source of ignition can creat a flash fire, not a UVCE (Unconfined Vapour Cloud Explosion).

Run off to sewer may cause fire or explosion hazard

Containers may explode in heat of fire. Use water to cool fire-exposed containers and to disperse vapour.

Printing date 16.03.2020 Revision: 05.10.2018

Trade name: 40-1706-10 Ethanol Spray (70% Ethanol)

(Contd. of page 2)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Keep ignition sources away - no smoking.

Wear protective equipment. Keep unprotected persons away.

Eliminate all sources of ignition.

Wear appropriate protective clothing.

Avoid breathing vapours.

Keep unnecessary people away; isolate hazard area and deny entry.

Stay up wind and keep out of low areas where vapour may accumulate and ignite.

For small spills take up with a non-combustible absorbant.

· 6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow product to reach sewage system or any water course in the undiluted form.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Allow to evaporate if it is safe to do so or contain and absorb using earth, sand or other inert material then transfer into suitable containers for recovery or disposal. Ventilate contaminated area thoroughly.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Avoid direct contact (skin/eye contact, ingestion and/or inhalation of fume/mist/dust) with the product in the undiluted form.

Suitable equipment for dealing with fires, spills and leaks must be readily available. .

Do not smoke eat or drink in areas of use and storage.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage:

· Requirements to be met by storerooms and receptacles:

Storage area should be cool, dry, well ventilated, out of direct sunlight and separated from oxidants and strong mineral acids.

Store in original containers.

Store away from sources of heat or ignition.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- \cdot Further information about storage conditions:

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Keep container tightly sealed.

Store in a bunded area.

 \cdot 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

Revision: 05.10.2018 Printing date 16.03.2020

Trade name: 40-1706-10 Ethanol Spray (70% Ethanol)

(Contd. of page 3)

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

64-17-5 Ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

WORKERS

Acute / short-term exposure - local effects

Inhalation DN(M)EL

- DNEL (Derived No Effect Level): 1900 mg/m³

Long-term exposure - systemic effects

Dermal DN(M)EL

- DNEL (Derived No Effect Level): 343 mg/kg bw/day

Inhalation DN(M)EL

- DNEL (Derived No Effect Level): 950 mg/m³

GENERAL POPULATION

Acute / short-term exposure - local effects

Inhalation DN(M)EL

- DNEL (Derived No Effect Level): 950 mg/m³

Long-term exposure - systemic effects

Dermal DN(M)EL

- DNEL (Derived No Effect Level): 206 mg/kg bw/day

Inhalation DN(M)EL

- DNEL (Derived No Effect Level): 114 mg/m³

Oral DN(M)EL

- DNEL (Derived No Effect Level): 87 mg/kg bw/day

· PNECs

PNEC aqua (freshwater): 0.96 mg/L

PNEC aqua (marine water): 0.79 mg/L

PNEC aqua (intermittent releases): 2.75 mg/L

PNEC STP: 580 mg/L

PNEC sediment (freshwater): 3.6 mg/kg sediment dw

PNEC sediment (marine water): 2.9 PNEC soil: 0.63 mg/kg soil dw

PNEC oral: 0.72 g/kg food

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

Select PPE appropriate for the operations taking place taking into account the product properties.

· General protective and hygienic measures:

Avoid close or long term contact with the skin.

Do not eat, drink, smoke or sniff while working.

A safe system of work must be formulated and followed to ensure safe working with this product. Relevant workers must receive suitable and sufficient training and supervision.

Take note of assigned Workplace Exposure Limits.

Pregnant women should strictly avoid inhalation or skin contact.

Ensure that eyewash stations and safety showers are close to the workstation location.

A safe system of work must be formulated and followed to ensure that workers who may be pregnant or breastfeeding do not come into direct contact with the product.

Wash hands before breaks and at the end of work.

• Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.

(Contd. on page 5)

Printing date 16.03.2020 Revision: 05.10.2018

Trade name: 40-1706-10_Ethanol Spray (70% Ethanol)

(Contd. of page 4)

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Wear gloves with breakthrough times >480 minutes: Nitrile rubber gloves. Butyl rubber gloves.(complying to EN 374-3)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Safety glasses
- · Body protection: Solvent resistant protective clothing

9.1 Information on basic physical and c	hemical properties
General Information	
Appearance:	
Form:	Fluid
Colour:	Colourless
Odour: Odour threshold:	Alcohol-like Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	-48 °C
Initial boiling point and boiling range	: 78 °C
Flash point:	21 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	350 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not self-igniting.
Explosive properties:	Product is not explosive. However, formation of explosive ai vapour mixtures are possible.
Explosion limits:	
Lower:	2.5 Vol %
Upper:	13.0 Vol %
Vapour pressure at 20 °C:	59 hPa
Density at 20 °C:	0.79 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Fully miscible.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.

Printing date 16.03.2020 Revision: 05.10.2018

Trade name: 40-1706-10 Ethanol Spray (70% Ethanol)

(Contd. of page 5)

Kinematic: Not determined.

• 9.2 Other information NOTE: The physical data presented above are typical values and

should not be construed as a specification.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous reactions

Forms explosive gas mixture with air.

Reacts slowly with calcium hypochlorite, silver oxide and ammonia. This generates fire and explosion hazard. Reacts violently with strong oxidants such as nitric acid, silver nitrate, mercuric nitrate and magnesium perchlorate. This generates fire and explosion hazard.

- 10.4 Conditions to avoid Aluminium at higher temperatures.
- 10.5 Incompatible materials: Strong acids and oxidising agents
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- $\cdot \ Serious \ eye \ damage/irritation$

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Subacute to chronic toxicity:

Effects of long-term or repeated exposure: The liquid defats the skin. The substance may have effects on the upper respiratory tract and central nervous system. This may result in irritation, headache, fatigue and lack of concentration.

Ethanol consumption during pregnancy may adversely affect the unborn child.

Chronic ingestion of ethanol may cause liver cirrhosis.

· Additional toxicological information:

Routes of exposure: The substance can be absorbed into the body by inhalation of its vapour and by ingestion. Inhalation risk: A harmful contamination of the air will be reached rather slowly on evaporation of this substance at 20 degs.C.

Effects of short-term exposure: The substance is irritating to the eyes. Inhalation of high concentrations of the vapour may cause irritation of the eyes and respiratory tract. The substance may cause effects on the central nervous system.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- $\cdot \textbf{STOT-single exposure} \ \text{Based on available data, the classification criteria are not met.} \\$
- $\cdot \textbf{STOT-repeated exposure} \text{ Based on available data, the classification criteria are not met.} \\$
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability biodegradable

(Contd. on page 7)

Printing date 16.03.2020 Revision: 05.10.2018

Trade name: 40-1706-10 Ethanol Spray (70% Ethanol)

(Contd. of page 6)

- 12.3 Bioaccumulative potential Product is not expected to bioaccumulate.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Recommended Hierarchy of Controls:

- Minimise waste;
- Reuse if not contaminated;
- Recycle, if possible; or
- Safe disposal (if all else fails).

Contact waste processors for recycling information.

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.

· European waste catalogue

Waste key numbers in accordance with the European Waste Catalogue (EWC) are origin-referred defined. Since this product is used in several industries, no waste key can be provided by the supplier. The waste key number should be determined in arrangement with your waste disposal partner or the responsible authority.

- · Uncleaned packaging:
- · Recommendation:

Container remains hazardous when empty. Continue to observe all precuations.

Containers, even those that are "empty," may contain residues that can develop flammable and/or hazardous vapours upon heating. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

Do not mix with other waste streams.

· Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information		
· 14.1 UN-Number · ADR, IMDG, IATA	UN1170	
· 14.2 UN proper shipping name		
· ADR	1170 ETHANOL SOLUTION (ETHYL ALCOHO)	
	SOLUTION)	
· IMDG	ETHANOL SOLUTION (ETHYL ALCOHO)	
	SOLUTION)	
· IATA	ETHANOL SOLUTION	

GB

Printing date 16.03.2020 Revision: 05.10.2018

Trade name: 40-1706-10 Ethanol Spray (70% Ethanol)

(Contd. of page 7)

- · 14.3 Transport hazard class(es)
- · ADR, IMDG, IATA



· Class	3 Flammable liquids.
	2

· Label 3

· 14.4 Packing group · ADR, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): 33
 EMS Number: F-E,S-D

· 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)
Transport category
Tunnel restriction code
D/E

• UN "Model Regulation": UN1170, ETHANOL SOLUTION (ETHYL ALCOHOL

SOLUTION), 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2